



WL2 Firewall®

Excellent purifying performance,
easy operation and stylish design

Purified water for the workplace

With a choice of hot and cold, the WL2 Firewall (WL2 FW) is the preferred solution for any small or medium-sized workplace, looking for great tasting water, reliability, and guaranteed quality.

Advanced technology

The WL2 FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T and to NSF/ANSI-53 for the reduction of lead, asbestos, and cysts, meaning they offer the best possible filtration.



Firewall

Waterlogic's patented Firewall technology features a highly effective UVC purification system that acts all the way through to the point of dispense. **Firewall guarantees water free from viruses and bacteria up to 99.9999%. Guaranteed effective against COVID-19.**



BioCote®* product protection

The key plastic surfaces, surrounding the dispensing area are infused with BioCote® technology, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



Certified purity for peace of mind

The Firewall technology has been certified by IAPMO R&T to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – **no other water cooler features these standards of certification** together. This means that **Firewall technology delivers the safest water possible** for the workplace.

*BioCote® silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote® does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

Firewall, patented UVC technology, reduces the risks of bacteria, viruses, and pathogens purifying the water up to 99.9999%

BioCote®* technology helps to keep Waterlogic dispensers fresh and clean for longer, by protecting them against odor causing microbes, such as bacteria, and mold

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

Water options

cold

hot



Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding

13.7" (W) x 40.3" (H) x 14.3" (D)

Countertop

13.7" (W) x 18.6" (H) x 14.3" (D)

Dispensing area height

9"

Weight (Hot and cold models)

Countertop: ~42 lbs

Freestanding: ~58 lbs

Standard filtration supplied

Carbon block with lead, cyst, and asbestos reduction

Storage capacity

Hot tank: 0.4 US gal

Cold tank (Freestanding): 1.06 US gal

Cold tank (Countertop): 0.53 US gal

Drip tray capacity

12.7 fl oz/360 ml

Compressor

Compressor (R134a) 120V/60Hz

Water temperatures settings

Cold: 37°/ 41°/ 45°F (default 41°F)

Hot: 185-189°F (default 185°C)

Number of users 10 - 30

Contact us today

Waterlogic Americas
www.waterlogicsusa.com
(855) 350-5518
info@waterlogicsusa.com

3175 Bass Pro Drive
Grapevine, TX 76051

Tested and certified



Firewall technology is certified by IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.**

*certificate may vary depending on different models or products